

TRIMFAST® HEAVY DUTY MODEL 210 / 210T







- Engineered for the power and durability required for use with light gauge steel
- Accepts t-nail style hardened trim pins
- Power to fasten to 14ga steel at the speed of nailing to wood
- Operates using typical jobsite air compressor at 115 psi maximum
- Capable of driving pins 1" to 2-1/2" long
- Select the Model 210T tool and the capacity increases to 3" long pins
- Systems approach with tools and fasteners provides single source responsibility
- Comes standard with plastic carrying case

**PIN TYPE**AST-100 TRIMFAST® HEAVY DUTY TRIM PINS



### **TOOL TYPE**



Model 210

Model 210T

### **TOOL CHARACTERISTICS**

Height	Width	Length	Weight
12"	3 1/2"	11 1/2"	6 lbs
305 mm	89 mm	292 mm	2.72 kg

**Pressure** 85 - 115 psi | 6 - 8 bar

**Lubricant** Non-detergent pneumatic tool lubricant

Recommended steel thickness 20 ga - 14 ga

# **FASTENER DATA:**

Pin Type	AST-100-0150G	AST-100-0200G	AST-100-0250G	AST-100-0300G*		
Wire	0.100"   2.54 mm					
Shank	Smooth					
Head	1/4"   6 mm					
Length	1 1/2"   39 mm	2"   50 mm	2 1/2"   63 mm	3"   75 mm		
Coating	Electro Galvanized					
Magazine Capacity	50 pins					

<sup>\*</sup> Requires Model 210T

### **ACTUATION & LOADING**

Actuation System\*

Sequential fire

Loading\*

Magazine with latch

\*see instruction manual

## **APPLICATIONS**

- James Hardie® XLD fiber cement trim to light gauge steel framing
- Miratec® treated exterior composite trim to light gauge steel framing
- Wood furring and exterior trim to light gauge steel framing
- Wood or metal furring to CMU

